



蝶式絕緣子

PORCELAIN SHACKLE INSULATORS




Fig1




Fig2




Fig3




Fig4

主要尺寸和性能 MAIN DIMENSIONS AND STANDARD PARTICULARS

型號 Type	圖號 Fig No	主要尺寸 Main dimensions(mm)					干閃電壓 Dry withstand voltage(kV)	濕閃電壓 Wet withstand voltage(kV)	擊穿電壓 Puncture voltage (kV)	機械破壞負荷 Mechanical strength(kN)	Packing	
		A	B	D	d	R					No. per	Mass(kg)
S.03	1	57	63	35	11	5	17	8	25	6,25	100	23
S.05	1	75	88	41	17	8	22	11	33	17,80	24	16
S.1	1	88	100	57	18	13	26	14	39	17,80	24	20
S.2	1	100	114	63	21	16	35	19	52	22,25	12	16

型號 Type	圖號 Fig No	主要尺寸(mm/") Main dimensions						機械破壞負荷(kg) Mechanical failing load	工頻閃絡電壓 (KV)(有效值) Power-fre- quency flashover voltage		重量(kg) Weight	釉色 Fired blank
		H	D	d	d1	d2	R		干 Dry	濕 Wet		
		ED-1	2	90	100	95	50	22	12	1200	22	10
ED-2	2	75	80	75	42	20	10	1000	18	9	0.40	白 White
ED-3	2	65	70	65	36	16	8	800	16	7	0.25	白 White
ED-4	2	50	60	55	30	16	6	500	14	6	0.15	白 White
ED-2(B)	3	76/3"	89/3 $\frac{1}{2}$ "	83/3 $\frac{9}{32}$ "	48/1 $\frac{7}{8}$ "	21/ $\frac{13}{16}$ "	10/ $\frac{13}{16}$ "	1300	-	-	0.48	棕 Brown
ED-2(B) ₁	3	76/3"	89/3 $\frac{1}{2}$ "	83/3 $\frac{9}{32}$ "	48/1 $\frac{7}{8}$ "	17.5/ $\frac{11}{16}$ "	10/ $\frac{13}{23}$ "	1300	-	-	0.50	棕 Brown
ED-2(C)	4	80/3 $\frac{5}{32}$ "	80/3 $\frac{5}{32}$ "	-	50/2"	22/ $\frac{7}{8}$ "	6/ $\frac{1}{4}$ "	1350	25	12	0.47	棕 Brown



Fuzhou LingT Trading Co., Ltd.

Add: No.1718 A2# Wanda Plaza, Aofeng Road, Fuzhou Fujian China.

Tel: 0086-591-87618322 Fax: 0086-591- 83965269

E-mail: lingt@fjever.com Website: www.fjever.com